

# TeeJet® Double Outlet Flat Spray Tips

150° Series  
Stainless Steel  
and Brass

Suggested for post-directed application with hose drops.



**How to order:**

Specify tip number and material

Example:

TQ150-03-SS      Stainless Steel



**List Price**

Nozzle Part#	Price
TQ150-**-SS (Stainless)	\$16.58
TQ150-** (Brass)	\$9.16

**Required Cap**

25612-\*-NYR      \$1.04

Quick TeeJet Cap & Seat Gasket Set  
\*Specify Cap Color

Icon	PSI	CAPACITY ONE NOZZLE IN GPM	GPA											
			4 MPH	5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	12 MPH	14 MPH	16 MPH	18 MPH	
TQ150-01-SS (100)	20	0.071	5.3	4.2	3.5	3.0	2.6	2.3	2.1	1.8	1.5	1.3	1.2	
	25	0.079	5.9	4.7	3.9	3.4	2.9	2.6	2.3	2.0	1.7	1.5	1.3	
	30	0.087	6.5	5.2	4.3	3.7	3.2	2.9	2.6	2.2	1.8	1.6	1.4	
	40	0.10	7.4	5.9	5.0	4.2	3.7	3.3	3.0	2.5	2.1	1.9	1.7	
TQ150-015-SS (100)	20	0.11	8.2	6.5	5.4	4.7	4.1	3.6	3.3	2.7	2.3	2.0	1.8	
	25	0.12	8.9	7.1	5.9	5.1	4.5	4.0	3.6	3.0	2.5	2.2	2.0	
	30	0.13	9.7	7.7	6.4	5.5	4.8	4.3	3.9	3.2	2.8	2.4	2.1	
	40	0.15	11.1	8.9	7.4	6.4	5.6	5.0	4.5	3.7	3.2	2.8	2.5	
TQ150-02-SS (100)	20	0.14	10.4	8.3	6.9	5.9	5.2	4.6	4.2	3.5	3.0	2.6	2.3	
	25	0.16	11.9	9.5	7.9	6.8	5.9	5.3	4.8	4.0	3.4	3.0	2.6	
	30	0.17	12.6	10.1	8.4	7.2	6.3	5.6	5.0	4.2	3.6	3.2	2.8	
	40	0.20	14.9	11.9	9.9	8.5	7.4	6.6	5.9	5.0	4.2	3.7	3.3	
TQ150-03-SS (100)	20	0.21	15.6	12.5	10.4	8.9	7.8	6.9	6.2	5.2	4.5	3.9	3.5	
	25	0.24	17.8	14.3	11.9	10.2	8.9	7.9	7.1	5.9	5.1	4.5	4.0	
	30	0.26	19.3	15.4	12.9	11.0	9.7	8.6	7.7	6.4	5.5	4.8	4.3	
	40	0.30	22	17.8	14.9	12.7	11.1	9.9	8.9	7.4	6.4	5.6	5.0	
TQ150-04-SS (50)	20	0.28	21	16.6	13.9	11.9	10.4	9.2	8.3	6.9	5.9	5.2	4.6	
	25	0.32	24	19.0	15.8	13.6	11.9	10.6	9.5	7.9	6.8	5.9	5.3	
	30	0.35	26	21	17.3	14.9	13.0	11.6	10.4	8.7	7.4	6.5	5.8	
	40	0.40	30	24	19.8	17.0	14.9	13.2	11.9	9.9	8.5	7.4	6.6	
TQ150-05-SS (50)	20	0.35	26	21	17.3	14.9	13.0	11.6	10.4	8.7	7.4	6.5	5.8	
	25	0.40	30	24	19.8	17.0	14.9	13.2	11.9	9.9	8.5	7.4	6.6	
	30	0.43	32	26	21	18.2	16.0	14.2	12.8	10.6	9.1	8.0	7.1	
	40	0.50	37	30	25	21	18.6	16.5	14.9	12.4	10.6	9.3	8.3	
TQ150-06-SS (50)	20	0.42	31	25	21	17.8	15.6	13.9	12.5	10.4	8.9	7.8	6.9	
	25	0.47	35	28	23	19.9	17.4	15.5	14.0	11.6	10.0	8.7	7.8	
	30	0.52	39	31	26	22	19.3	17.2	15.4	12.9	11.0	9.7	8.6	
	40	0.60	45	36	30	25	22	19.8	17.8	14.9	12.7	11.1	9.9	
TQ150-08-SS (50)	20	0.57	42	34	28	24	21	18.8	16.9	14.1	12.1	10.6	9.4	
	25	0.63	47	37	31	27	23	21	18.7	15.6	13.4	11.7	10.4	
	30	0.69	51	41	34	29	26	23	20	17.1	14.6	12.8	11.4	
	40	0.80	59	48	40	34	30	26	24	19.8	17.0	14.9	13.2	
TQ150-09-SS (50)	20	0.64	48	38	32	27	24	21	19.0	15.8	13.6	11.9	10.6	
	25	0.71	53	42	35	30	26	23	21	17.6	15.1	13.2	11.7	
	30	0.78	58	46	39	33	29	26	23	19.3	16.5	14.5	12.9	
	40	0.90	67	53	45	38	33	30	27	22	19.1	16.7	14.9	
50	1.01	75	60	50	43	37	33	30	25	21	18.7	16.7		

# TeeJet® Off-Center Flat Spray Tips — Smaller Capacities

TeeJet Off-Center spray tips are commonly installed in double and single swivel nozzle bodies. Because these bodies are adjustable for angular position, a wide spray swath is easily obtained.



**How to order:**

Specify tip number and material

Example:

OC-02                      Brass  
OC-SS06                 Stainless Steel

**List Price**

Nozzle Part#	Price
OC-SS** (Stainless)	\$16.58
OC-** (Brass)	\$11.21

**Required Cap**

25612-\*-NYR      \$1.04

Quick TeeJet Cap & Seat Gasket Set  
\*Specify Cap Color

Icon	PSI	CAPACITY ONE NOZZLE IN GPM	HEIGHT = 18"						HEIGHT = 24"													
			GPA						GPA													
			"W" IN INCHES		3 MPH		4 MPH		5 MPH		6 MPH		"W" IN INCHES		3 MPH		4 MPH		5 MPH		6 MPH	
OC-01 (100)	30	0.087	58	3.0	2.2	1.8	1.5	65	2.7	2.0	1.6	1.3	65	2.7	2.0	1.6	1.3	65	2.7	2.0	1.6	1.3
	40	0.10	60	3.3	2.5	2.0	1.7	67	3.0	2.2	1.8	1.5	67	3.0	2.2	1.8	1.5	67	3.0	2.2	1.8	1.5
	60	0.12	62	3.8	2.9	2.3	1.9	69	3.4	2.6	2.1	1.7	69	3.4	2.6	2.1	1.7	69	3.4	2.6	2.1	1.7
OC-02 (50)	30	0.17	68	5.0	3.7	3.0	2.5	75	4.5	3.4	2.7	2.2	75	4.5	3.4	2.7	2.2	75	4.5	3.4	2.7	2.2
	40	0.20	70	5.7	4.2	3.4	2.8	77	5.1	3.9	3.1	2.6	77	5.1	3.9	3.1	2.6	77	5.1	3.9	3.1	2.6
	60	0.24	72	6.6	5.0	4.0	3.3	78	6.1	4.6	3.7	3.0	78	6.1	4.6	3.7	3.0	78	6.1	4.6	3.7	3.0
OC-03 (50)	30	0.26	77	6.7	5.0	4.0	3.3	80	6.4	4.8	3.9	3.2	80	6.4	4.8	3.9	3.2	80	6.4	4.8	3.9	3.2
	40	0.30	80	7.4	5.6	4.5	3.7	83	7.2	5.4	4.3	3.6	83	7.2	5.4	4.3	3.6	83	7.2	5.4	4.3	3.6
	60	0.37	82	8.9	6.7	5.4	4.5	85	8.6	6.5	5.2	4.3	85	8.6	6.5	5.2	4.3	85	8.6	6.5	5.2	4.3
OC-04 (50)	30	0.35	91	7.6	5.7	4.6	3.8	93	7.5	5.6	4.5	3.7	93	7.5	5.6	4.5	3.7	93	7.5	5.6	4.5	3.7
	40	0.40	93	8.5	6.4	5.1	4.3	94	8.4	6.3	5.1	4.2	94	8.4	6.3	5.1	4.2	94	8.4	6.3	5.1	4.2
	60	0.49	94	10.3	7.7	6.2	5.2	95	10.2	7.7	6.1	5.1	95	10.2	7.7	6.1	5.1	95	10.2	7.7	6.1	5.1
OC-06 (50)	30	0.52	99	10.4	7.8	6.2	5.2	108	9.5	7.2	5.7	4.8	108	9.5	7.2	5.7	4.8	108	9.5	7.2	5.7	4.8
	40	0.60	101	11.8	8.8	7.1	5.9	110	10.8	8.1	6.5	5.4	110	10.8	8.1	6.5	5.4	110	10.8	8.1	6.5	5.4
	60	0.73	102	14.2	10.6	8.5	7.1	111	13.0	9.8	7.8	6.5	111	13.0	9.8	7.8	6.5	111	13.0	9.8	7.8	6.5
OC-08 (50)	30	0.69	100	13.7	10.2	8.2	6.8	110	12.4	9.3	7.5	6.2	110	12.4	9.3	7.5	6.2	110	12.4	9.3	7.5	6.2
	40	0.80	102	15.5	11.6	9.3	7.8	112	14.1	10.6	8.5	7.1	112	14.1	10.6	8.5	7.1	112	14.1	10.6	8.5	7.1
	60	0.98	104	18.7	14.0	11.2	9.3	113	17.2	12.9	10.3	8.6	113	17.2	12.9	10.3	8.6	113	17.2	12.9	10.3	8.6
OC-12	30	1.04	102	20	15.1	12.1	10.1	113	18.2	13.7	10.9	9.1	113	18.2	13.7	10.9	9.1	113	18.2	13.7	10.9	9.1
	40	1.20	104	23	17.1	13.7	11.4	115	21	15.5	12.4	10.3	115	21	15.5	12.4	10.3	115	21	15.5	12.4	10.3
	60	1.47	105	28	21	16.6	13.9	116	25	18.8	15.1	12.5	116	25	18.8	15.1	12.5	116	25	18.8	15.1	12.5
OC-16	30	1.39	132	21	15.6	12.5	10.4	142	19.4	14.5	11.6	9.7	142	19.4	14.5	11.6	9.7	142	19.4	14.5	11.6	9.7
	40	1.60	138	23	17.2	13.8	11.5	146	22	16.3	13.0	10.8	146	22	16.3	13.0	10.8	146	22	16.3	13.0	10.8
	60	1.96	143	27	20	16.3	13.6	148	26	19.7	15.7	13.1	148	26	19.7	15.7	13.1	148	26	19.7	15.7	13.1