



PEDESTAL MOUNT CENTRIFUGAL PUMPS

Self-Priming Hydraulic Driven Pumps



Model Number	Max. GPM	Max. PSI	Description	Estimated Weight Ea.	List Price
9303C-HM1C-SP	122	130	13 gpm hydraulic motor/cast iron pump for open/closed center systems, ports (NPT): 1½" inlet, 1½" outlet.	38 lbs.	\$ 1181.00
9303C-HM2C-SP	104	90	6 gpm hydraulic motor/cast iron pump for closed center systems, ports (NPT): 1½" inlet, 1½" outlet.	38 lbs.	\$ 1181.00
9303C-HM3C-SP	120	95	20 gpm hydraulic motor/cast iron pump, Large open center systems, ports (NPT): 1½" inlet, 1½" outlet.	38 lbs.	\$ 1236.00
9303C-HM4C-SP	99	97	7 gpm hydraulic motor/cast iron pump, open/closed center systems, ports (NPT): 1½" inlet, 1½" outlet.	38 lbs.	\$ 1181.00
9303C-HM5C-SP	140	140	16 gpm hydraulic motor/cast iron pump, open/closed center systems, ports (NPT): 1½" inlet, 1½" outlet.	39 lbs.	\$ 1181.00
9305C-HM3C-SP	178	154	19 gpm hydraulic motor/cast iron pump, large open center systems, ports (NPT): 2" inlet, 2" outlet.	59 lbs.	\$ 1832.00
9305C-HM3C-BSP	178	154	19 gpm hydraulic motor/cast iron pump, large open center systems, ports (BSP): 2" inlet, 2" outlet.	59 lbs.	\$ 1832.00
3430-0589	Silicon seal and o-ring			3 oz.	\$ 154.75
3430-0480SP	Self-Priming chamber kits for Model 9300			27 lbs.	\$ 218.75
3430-0481SP	Self-Priming chamber kits for Model 9305			37 lbs.	\$ 833.00
3430-0551	Silicon carbide seal kit for 9305C-HM3C-SP and BSP only			3 oz.	\$ 171.00

**LIST PRICE
CALL FOR DISCOUNTS!**

Add suffix letter "B" for silicon carbide seal (ie: 9303C-HM3C-BSP)

12-Volt Clutch Activated Pedestal Pumps



9262C-C*	88	124	5000	Pedestal mount, cast iron pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, 1½" NPT inlet, 1" NPT outlet, counterclockwise rotation.	22 lbs.	\$ 711.00
9263C-C**	140	124	5000	Pedestal mount, cast iron pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, 1½" NPT inlet, 1½" NPT outlet, counterclockwise rotation.	23 lbs.	\$ 717.00
9263C-CR*	140	124	5000	Pedestal mount, cast iron pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, (2526-0010) 1½" NPT inlet, 1½" NPT outlet, clockwise rotation.	21 lbs.	\$ 727.00
3430-0332	Seal and o-ring repair kit.			3 oz.	\$ 42.25	
3430-0333	Seal and o-ring repair kit for polypropylene pump.			4 oz.	\$ 54.00	
3430-0589	Silicon seal kit - cast iron model only.			3 oz.	\$ 154.75	

Series 9200 Self-Priming Pedestal Pumps with 12 Volt Clutch



Model Number	Max. GPM	Max. PSI	Max. RPM	Description	Estimated Weight Ea.	List Price
9263C-C-SP	120	157	5000	Pedestal mount, cast iron pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, 1½" NPT inlet, 1½" NPT outlet, counterclockwise rotation.	44 lbs.	\$ 1027.00
9263C-CR-SP	140	155	5000	Pedestal mount, cast iron pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, (2526-0010) 2" NPT inlet, 2" NPT outlet, clockwise rotation.	42 lbs.	\$ 1037.00
3430-0589	Silicon seal kit - cast iron model only			3 oz.	\$ 154.75	

Add suffix letter "B" for silicon carbide seal (i.e. 9253C-C-SP-B)

Series 9200 Stainless Steel, Pedestal Mount with 12 Volt Clutch



Model Number	Max. GPM	Max. PSI	Description	Estimated Weight Ea.	List Price
9262S-C	88	124	Pedestal mount, stainless steel pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, 1½" NPT inlet, 1" NPT outlet, counterclockwise rotation.	22 lbs.	\$ 1112.00
9263S-C	140	124	1½" x 1½" centrifugal pump 316 stainless steel constructed with 12 VDC clutch	23 lbs.	\$ 1118.00
9263S-CR	140	124	Pedestal mount, stainless steel pump with 12 volt heavy duty clutch with 5" diameter A-section pulley, (2526-0010) 1½" NPT inlet, 1½" NPT outlet, clockwise rotation.	23 lbs.	\$ 1128.00

PEDESTAL MOUNT CENTRIFUGAL PUMPS



Series 9200 Cast Iron, Pedestal-Mount Models



New!

Model Number	Max. GPM	Max. PSI	Max. RPM	Description	Estimated Weight Ea.	List Price
9202C*	105	170	6000	Pedestal mount, cast iron pump with 5/8" solid shaft and Viton shaft seal. 1 1/2" Inlet; 1" outlet NPT ports.	18 lbs.	\$ 386.00
9203C*†	136	170	6000	Pedestal mount, cast iron pump with 5/8" solid shaft and Viton shaft seal. 1 1/2" Inlet, 1 1/2" outlet NPT ports.	19 lbs.	\$ 391.00
9203C-R*	136	170	6000	Pedestal mount, clockwise rotation cast iron pump, with 5/8" solid shaft, Viton seal and 1 1/2" x 1 1/2" NPT ports.	17 lbs.	\$ 401.00
9204C*	190	80	4200	Pedestal mount, cast iron pump with 5/8" solid shaft and Viton shaft seal. 2" Inlet, 1 1/2" outlet NPT ports.	20 lbs.	\$ 513.00
9205C*	180	190	4200	Pedestal mount, cast iron pump with 7/8" solid keyed shaft, Viton seal, and 2" inlet x 1 1/2" outlet NPT ports.	47 lbs.	\$ 986.00
9206C*†	225	80	4200	Pedestal mount, cast iron pump with 5/8" solid shaft and Viton shaft seal. 2" Inlet, 1 1/2" outlet NPT ports.	23 lbs.	\$ 513.00
3430-0332	Seal and o-ring repair kit ceramic.				3 oz.	\$ 42.25
3430-0537	Seal and o-ring repair kit for 9205C only.				4 oz.	\$ 39.00
3430-0589	Silicone carbide kit.				3 oz.	\$ 154.75

Series 9200 Self-Priming, Cast Iron, Pedestal Mount Pumps



Model Number	Max. GPM	Max. PSI	Max. RPM	Description	Estimated Weight Ea.	List Price
9203C-R-SP*	140	155	5500	Pedestal mount, clockwise rotation cast iron pump, with 5/8" solid shaft, Viton seal and 2" x 2" NPT ports.	38 lbs.	\$ 711.00
9203C-SP*	120	157	5500	Self-priming, pedestal mount, cast iron pump with 5/8" solid shaft and Viton shaft seal. 1 1/2" Inlet, 1 1/2" outlet NPT ports.	38 lbs.	\$ 701.00
9205C-SP	180	120	3800	Self-priming, pedestal mount, cast iron pump with 7/8" solid keyed shaft, Viton seal, and 2" inlet x 2" outlet NPT ports.	48 lbs.	\$ 1341.00
9205C-BSP	180	120	3800	Self-priming, pedestal mount, cast iron pump with 7/8" solid keyed shaft, Viton seal, and 2" x 2" BSP ports.	48 lbs.	\$ 1341.00
3430-0480SP	Self-priming chamber kit for Model 9203C.				27 lbs.	\$ 218.75
3430-0481SP	Self-priming chamber kit for Model 9205C.				37 lbs.	\$ 833.00
3430-0482SP	Self-priming chamber kit for reverse rotation ONLY.				26 lbs.	\$ 645.25

*Add suffix letter "B" for Life Guard™ Silicon Carbide Seal.

Series 9200 Stainless Steel, Pedestal-Mount Models



Model Number	Max. GPM	Max. PSI	Max. RPM	Description	Estimated Weight Ea.	List Price
9202S	105	170	6000	Pedestal mount, stainless steel pump with 5/8" solid shaft and Viton shaft seal. 1 1/2" Inlet; 1" outlet NPT ports.	18 lbs.	\$ 759.00
9203S	136	170	6000	Pedestal mount, 316 stainless steel pump with 5/8" solid shaft and Viton silicon carbide shaft seal. Ports (NPT): 1 1/2" inlet, 1 1/2" outlet	19 lbs.	\$ 764.00
9203S-R	136	170	6000	Pedestal mount, clockwise rotation, 316 stainless steel pump with 5/8" solid shaft and Viton silicon carbide shaft seal. Ports (NPT): 1 1/2" inlet, 1 1/2" outlet	37 lbs.	\$ 774.00
9206S	225	80	4200	Pedestal mount, 316 stainless steel pump with 5/8" solid shaft and Viton silicon carbide shaft seal. Ports (NPT): 2" inlet, 1 1/2" outlet	23 lbs.	\$ 915.00

Model Number	Max. GPM	Max. PSI	Max. RPM	Description	List Price	Estimated Shpg. Wt.
9600C	100	100	1200	High-capacity Turbine Pump made of cast iron with Valox® impeller, Viton lip seals and stainless steel 15/16" shaft and 1/4" key way.	\$491.00	28 lbs.
1320-0080			1200	1-3/4" Forged Steel PTO Adapter	58.00	1 lb.
1320-0078			1200	1-3/8" Forged Steel PTO Adapter	38.00	1 lb.
3430-0346				Torque Arm Kit for 9600C.	41.00	2 lbs.
3430-0347				Seal and o-ring repair kit.	24.25	4 oz.
0400-9600P				Valox impeller.	81.25	1 lb.

9600 Turbine

